


Papuci izolati tip auto

■ Papuci cupru izolati, tip ochi , 0.1 - 6 mm²

- Intarit in zona de sertizare
- Pentru conductoare multifilare fine si extrafine

Caracteristici


- Produs conf. normei DIN 46237
- Izolate, fara halogenuri
- Temperatura de lucru: pana la 70° C

Material

- Cu-ETP
- Izolatie: PVC

Suprafata

- Stanata



Sectie mm ²	Cod	Culoare	Cote conf. DIN	d1	d2	d3	d4	l	a1	a2	s	Greutate/ 100 buc ~ kg	buc/pac
0.1-0.4	X619/2	■	--	1.0	2.3	5.0	2.2	14.0	--	--	0.5	0.020	100
	X619/2.5	■	--	1.0	2.6	5.0	2.2	14.0	--	--	0.5	0.020	100
	X619/3	■	--	1.0	3.3	5.0	2.2	14.0	--	--	0.5	0.020	100
	X619/3.5	■	--	1.0	3.8	6.5	2.2	16.0	--	--	0.5	0.025	100
	X619/4	■	--	1.0	4.4	7.0	2.2	16.0	--	--	0.5	0.025	100
	X619/5	■	--	1.0	5.4	8.0	2.2	15.0	--	--	0.5	0.025	100
0.5-1	X620/2.5	■	2.5-1	1.6	2.8	6.0	3.2	16.5	5	10.5	0.8	0.060	100
	X620/3	■	3.0-1	1.6	3.2	6.0	3.2	16.5	5	10.5	0.8	0.060	100
	X620/3.5	■	3.5-1	1.6	3.7	6.0	3.2	16.5	5	10.5	0.8	0.550	100
	X620/4	■	4.0-1	1.6	4.3	8.0	3.2	17.5	5	10.5	0.8	0.070	100
	X620/5	■	5.0-1	1.6	5.3	10.0	3.2	18.5	5	10.5	0.8	0.090	100
	X620/6	■	--	1.6	6.5	11.0	3.2	20.5	5	10.5	0.8	0.080	100
	X620/8	■	--	1.6	8.4	14.0	3.2	22.5	5	10.5	0.8	0.130	100
	X620/10	■	--	1.6	10.5	18.0	3.2	24.5	5	10.5	0.8	0.130	100
1.5-2.5	X630/3	■	3.0-2.5	2.3	3.2	6.0	3.9	17.5	5	11.5	0.8	0.065	100
	X630/3.5	■	3.5-2.5	2.3	3.7	6.0	3.9	17.5	5	11.5	0.8	0.065	100
	X630/4	■	4.0-2.5	2.3	4.3	8.0	3.9	18.5	5	11.5	0.8	0.080	100
	X630/5	■	5.0-2.5	2.3	5.3	10.0	3.9	20.5	5	11.5	0.8	0.090	100
	X630/6	■	6.0-2.5	2.3	6.5	11.0	3.9	22.5	5	11.5	0.8	0.110	100
	X630/8	■	8.0-2.5	2.3	8.4	14.0	3.9	23.5	5	11.5	0.8	0.130	100
	X630/10	■	--	2.3	10.5	18.0	3.9	25.5	5	11.5	0.8	0.160	100
4-6	X650/4	■	4.0-6	3.6	4.3	8.0	5.6	20.5	6	12.5	1.0	0.140	100
	X650/5	■	5.0-6	3.6	5.3	10.0	5.6	21.5	6	12.5	1.0	0.160	100
	X650/6	■	6.0-6	3.6	6.5	11.0	5.6	22.5	6	12.5	1.0	0.170	100
	X650/8	■	8.0-6	3.6	8.4	14.0	5.6	25.5	6	12.5	1.0	0.220	100
	X650/10	■	10.0-6	3.6	10.5	18.0	5.6	27.5	6	12.5	1.0	0.290	100