



Caracteristici Principale

Gama de produse	Sedna
Tip produs sau componenta	Priza
Prezentare dispozitiv	Produs complet
Configuratie poli priza	2P + E cu obturatoare
Descriere priza standard	Legare la pamant laterala
Curent nominal	16 A - 250 V c.a.
Tenta de culoare placa de acoperire	Alb
Conexiuni - borne	Borne lift

Complementare

Montare dispozitiv de conectare	Incastrat
Gama de puteri	3680 W
Numar de cabluri	2 x 2.5 mm ²
Rigiditate cablu	Flexibil Rigid Impletit solid
Lungime de dezizolare conductor	13 mm
Material	ASA + PC
Finisaj suprafata	Glossy
Mod de fixare	Suruburi Suruburi Claws, span of claws working range : 52...69 mm
Inaltime	120 mm
Latime	84 mm
Adancime	48 mm
Adancimea proiectata	23.3 mm
Greutate produs	0.1031 kg

Mediu

standarde	IEC 60884-1
grad de protectie IP	IP20

Durabilitatea ofertei

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1715 - Schneider Electric declaration of conformity
REACH	Referinta nu contine SVHC peste prag
Profil de mediu pentru produs	Disponibil
Instructiuni sfarsit de viata produs	Nu necesita operatii specifice de reciclare

Contractual warranty

Perioada	18 luni
----------	---------